

MOL Dynamic Gold DX 5W-20

synthetic motor oil



MOL Dynamic Gold DX 5W-20 is a premium performance, fuel saving synthetic engine oil produced with dual lubricating film technology from synthetic base oils and a complex additive system, ensuring excellent flow characteristics, for use in the most advanced automobile engines. Its advantages can be fully exploited in the latest engines manufactured with narrow clearances. It is a special low viscosity engine oil therefore it is not recommend for certain engine types.

Please refer to the relevant recommendations of the engine manufacturers!

Application



- The most modern Opel/GM/Chevrolet gasoline engines
- For all Chrysler/Dodge/Jeep vehicles from 2005
- Hybrid gasoline and equipped with start-stop automatic vehicles
- Latest gasoline passenger cars and light commercial vehicles.
- Turbo charged, direct fuel injection engines
- The most advanced gasoline engines with narrow clearances

Features and benefits

| | |
|---|---|
| Dual lubricating film technology | Prevents contact and wear of metal surfaces by forming a liquid film in normal engine operation and a molecular protective layer in case of extreme loads |
| Low HTHS viscosity | Contributes to reduced fuel consumption, together with outstanding antiwear protection |
| Extremely long oil lifetime | Frequency of downtimes, operational costs, and environmental impact can be reduced |
| Low volatility | Lowers engine oil consumption and reduces the emission of harmful substances Economical operation |
| Extreme cold flow properties | Provides easy start-up, even in extreme cold, to extend the life of the car battery |
| Exceptional thermal and oxidation stability | Reduces the formation of sludge at low temperatures and of deposits at high temperatures |

Specifications and approvals

Viscosity grade: SAE 5W-20
API SP
Opel OV 040 1547 - A20
Ford WSS-M2C-960-A1
Chrysler MS-6395
ILSAC GF-6A

MOL Dynamic Gold DX 5W-20

synthetic motor oil



Properties

| Properties | Typical values |
|--|----------------|
| Density at 15°C [g/cm ³] | 0,847 |
| Kinematic viscosity at 40 °C [mm ² /s] | 45,4 |
| Kinematic viscosity at 100 °C [mm ² /s] | 8,2 |
| Viscosity index | 156 |
| Pour point [°C] | -39 |
| Flash point (Cleveland) [°C] | 230 |

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C