

MOL Formoil Asphalt

mould release oil



MOL Formoil Asphalt mould release agent contains optimized mixture of additives which ensure effective separation and corrosion inhibitors.

It can be used on surfaces contacting asphalt in order to prevent sticking of the asphalt to the surfaces. Prevents the build-up of asphalt and many other substances on truck beds.

It can be applied by spraying, rollers or brushes.

Application



Producing and using asphalt

Features and benefits

Application specific composition	Prevents the sticking of asphalt to the surfaces Easy to remove the bitumen from surfaces in case of sticking
Easy to lay on surfaces	Application to the mould surface is possible by spraying, rolling or brushing
Good flow properties	Applicable both outdoors and indoors
Good corrosion protection	Prevents rusting of mould elements and increases their lifetime

Properties

Properties	Typical values
Appearance	light yellow, bright, clear
Kinematic viscosity at 40°C [mm ² /s]	18
Flash point (Cleveland) [°C]	200

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

In the original container under the recommended storage conditions: 24 months

Recommended storage temperature: max. 40°C