

MOL GMO AL 15W-40

gas engine oil



MOL GMO AL 15W-40 is an ash-free gas engine oil produced from extra high quality additive components, developed for two-stroke gas engines.

Application



Two-stroke naturally aspirated or turbocharged natural gas engines requiring an ashless engine oil

Two-stroke gas engines manufactured by Ajax, Clark, Cooper-Bessemer or Fairbanks-Morse

Features and benefits

Excellent wear protection

Improves engine reliability and provides protection to critical engine parts

Protection against nitration

Prevents formation of sludge and deposits

Good cleaning effect

Keeps engine parts clean and prevents spark plug fouling

Excellent cold flow properties

Excellent pumpability

Improved corrosion protection

Prevents harmful effects of acidic combustion products

Specifications and approvals

Viscosity grade: SAE 15W-40
API CC

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,878
Kinematic viscosity at 40°C [mm ² /s]	107,5
Kinematic viscosity at 100 °C [mm ² /s]	14,3
Pour point [°C]	-33
Flash point (Cleveland) [°C]	240

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C