

MOL Outboard 2T

two stroke boat and Jet-ski motor oil



MOL Outboard 2T is an engine oil produced from highly refined mineral oils, using ash-free additives that ensure a high engine performance level, containing a pre-diluted component, developed for boat and jet-ski engines.

Application

Two-stroke water-cooled outboard and Jet-ski engines

Features and benefits

Ashless formulation	Reduces emission of smoke and harmful gases from the engine
Excellent corrosion protection	Maximum engine protection, even during extended storage
Outstanding cleaning effect	Prevents spark plug fouling and retards exhaustion system blockage
Good wear protection	Reliable equipment protection and long machine lifetime

Specifications and approvals

NMMA TC-W3

Properties

Properties	Typical values
Density at 15°C [g/cm ³]	0,873
Kinematic viscosity at 40°C [mm ² /s]	43,4
Kinematic viscosity at 100 °C [mm ² /s]	6,7
Pour point [°C]	-39
Flash point (Cleveland) [°C]	115

The characteristics in table are typical values of the product and do not constitute a specification.

Storage and handling instructions

Store in the original container in dry, properly ventilated area.

Keep away from direct flame and other sources of ignition.

Protect from direct sunlight.

During transport, storage and use of the product follow the work safety instructions and environmental regulations relating to mineral oil products.

For further details please read the Material Safety Data Sheet of the product.

Engine oils are finished lubricant formulations where additional additives are unnecessary and may result in unforeseeable adverse effects.

The manufacturer and distributor shall not be held liable for such possible damages.

In the original container under the recommended storage conditions: 60 months

Recommended storage temperature: max. 40°C